



Tsunami® QuickBridge 8200 Series

## Wireless Product Portfolio

- **Tsunami® 8000 Series** – PtP & PtMP product line delivering 300 Mbps plus data rate
- **Tsunami® .11 Series** – Our best selling Point-to-point and multipoint product line
- **Tsunami® GX800**– Carrier-class IP Ethernet bridge for voice and data backhaul for service providers and enterprise applications
- **Tsunami® QB 62000**– High capacity, small footprint PtP backhaul solution with 1Gbps throughput
- **ORINOCO® AP** - The industry's highest performance 802.11a/b/g/n access points

Proxim Wireless is a global pioneer of end-to-end broadband wireless systems that deliver the quadruple play. From Wi-Fi to wireless Gigabit Ethernet – our WLAN, Mesh, WiMAX and point-to-point products are available through our extensive global channel networks.

## Next generation of field-proven Tsunami® 8000 Wireless Backhaul Solution that Exceeds 4G Speed Requirements with 300 Mbps data rate!

The Tsunami® QB-8200, is a high power, extremely reliable and a cost-effective, non-line-of-sight 4G point-to-point (PtP) wireless backhaul solution. It delivers data rates of 300 Mbps, along with excellent spectrum and 25.8 dBm high power radios for extend coverage.

With its incredible channel capacity & flexibility, excellent spectrum efficiency and a highly evolved prioritization platform tailored to deliver voice, video and data applications, the Tsunami® QB-8200 satisfies carriers, wireless service providers and Government organizations with requirements for fast and reliable wireless backhaul.

The Tsunami® QB-8200 leverages the advantages of OFDM, MIMO radio innovations and Proxim's proprietary Wireless Outdoor Routing Protocol (WORP®) to provide wireless performance in excess of 4G products on the markets today.

### World-class Performance

- Point-to-Point system that delivers 300 Mbps data rate at distances of over 5 miles (8 km)
- Very low latency of 2 to 3 ms to support voice and video applications over long distances
- Built-in feature rich network protocols for bridging, routing and gateway functionality

### Non-Line-of-Sight and Advanced Features

- Non-line-of-sight capable, utilizing OFDM and enhanced 3x3 MIMO techniques to better penetrate through obstructions
- Features dual Gigabit Ethernet ports with PoE out to power other devices like surveillance cameras or additional radios
- Enables packet identification to create unique and sophisticated service rules and tiered service classes with ease
- Spectrum analyzer to help study frequency bands for interference, and select a relatively low interference channel.

### Frequency Agnostic

- Operates in licensed and unlicensed frequency bands
- Flexible channel planning with 5, 10, 20 and 40MHz size
- Provides support for extended frequency bands from 4.900 to 5.925 GHz

### Carrier-Grade Security

- Implements tiered security layers for the most secure outdoor wireless communications in the unlicensed frequency spectrum
- Utilizes Proxim's Wireless Outdoor Routing Protocol (WORP®), which prevents snooping, and features highly-secure remote management via SSL, SSH and SNMPv3
- Provides military-grade security with AES encryption technology, prevents unsecure client-to-client communications and leverages MAC, Ethertype and IP address packet filtering for granular network security

### Cost Effective and Ease of Use for Quick Return on Investment

- Suitable for the carriers, WISP and Government markets
- Certified for deployments in the Americas, Europe and Asia
- The most cost-effective, high performance point-to-point solution from Proxim, enabling any deployment to enjoy a quick return on investment

### Product Line Compatibility

- Connects to existing Tsunami® QB 8100

# Tsunami® QuickBridge 8200 Series

## Technical Specifications

<b>PRODUCT MODELS</b>					
QB-8200-LNK	Tsunami® QB 8200 Link, 300 Mbps, MIMO 3x3, Type-N Connectors (Two QB-8200-EPA)				
QB-8250-LNK	Tsunami® QB 8250 Link, 300 Mbps, MIMO 2x2, 23 dBi Integrated Antenna (Two QB-8250-EPR)				
<b>INTERFACES</b>					
WIRED ETHERNET	Two auto MDI-X RJ45 10/100/1000Mbps Ethernet - Port #1 with PoE in & Data - Port #2 with PoE out (802.3af pin out) & Data				
WIRELESS PROTOCOL	WORP® (Wireless Outdoor Router Protocol)				
<b>RADIO &amp; TX SPECS</b>					
MIMO	3x3MIMO				
MODULATION	OFDM				
FREQUENCY	4.900 – 5.925 GHz (Subject to Country Regulations)				
CHANNEL SIZE	40 MHz, 20 MHz, 10 MHz*, 5 MHz* channel bandwidths * Not applicable for DFS Band				
DATA RATE	MCS 0 to 15 for High Throughput mode (6.5 – 300 Mbps) with Dynamic Data Rate Selection				
TX POWER	Up to 25.8 dBm (Triple chain)				
TX POWER CONTROL	0 – 25 dB, in 0.5 dB steps. Automatic TPC with configurable EIRP limit				
RX SENSITIVITY (BER=10 <sup>-5</sup> )	Channel Size	40 MHz	20 MHz	10 MHz	5 MHz
	MCS 0	-85 dBm	-90 dBm	-92 dBm	-95 dBm
	MCS 7	-68 dBm	-71 dBm	-73 dBm	-76 dBm
	MCS 8	-85 dBm	-88 dBm	-90 dBm	-93 dBm
	MCS 15	-66 dBm	-69 dBm	-71 dBm	-74 dBm
LATENCY	< 3 msec				
ANTENNA	Model QB-8200-EPA: three N-Type Antenna Connectors with built in Surge Protection Model QB-8250-EPR: includes an Integrated 2x2 MIMO 23dBi Dual Polarized Antenna				
<b>MANAGEMENT</b>					
LOCAL	RS-232 serial (RJ11 to DB-9 dongle provided)				
REMOTE	Telnet and SSH, Web GUI and SSL, TFTP, SNMPv3				
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB				
OTHER	Syslog, sFlow™ agent, SNTP and local time, Spectrum analyzer				
<b>SECURITY</b>					
ENCRYPTION	AES-CCM 128 bits				
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication				
<b>NETWORK</b>					
MODES	Bridging (support LACP through external switches), Routing (RIP v2 and IP tunneling)				
THROUGHPUT	Model QB-8200-EPA and QB-8250-EPR: up to 246 Mbps				
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs				
QoS	Asymmetric Bandwidth Control	Uplink and Downlink CIR Control "committed information rate" per service flow Uplink and Downlink MIR Control "maximum information rate" per service flow			
	Packet Classification Capabilities	802.1D/802.1Q/802.1p priority, IPTOS, VLAN ID, IP source/destination address, source/destination port, Ethernet source/destination address, IP protocol, and Ethertype			
	Scheduling	Best Effort, Real Time Polling Services			
VLAN	802.1Q: Management VLAN. Transparent, Access, Trunk and Mixed mode. QinQ double tagging				
POWER CONSUMPTION	12 Watt typical (22 Watt max)				
<b>ENVIRONMENTAL SPECS</b>					
<b>TEMPERATURE</b>					
OPERATING	-40° to 60°C (-40° to 140° Fahrenheit)				
STORAGE	-55° to 80°C (-67° to 176° Fahrenheit)				
HUMIDITY	Max 100% relative humidity (non-condensing)				
WIND LOADING	125 mph				
WATER & DUST PROOF	IP67				
<b>PHYSICAL SPECS</b>					
<b>DIMENSIONS</b>					
PACKAGED	Model QB-8200-EPA: 14.56 x 13.69 x 8.18 in. (370 x 348 x 208 mm) Model QB-8250-EPR: 15.94 x 15.94 x 9.21 in. (405 x 405 x 234 mm)				
UNPACKAGED	Model QB-8200-EPA: 10.79 x 11.14 x 3.38 in (274 x 283 x 86 mm) Model QB-8250-EPR: 14.17 x 14.17 x 3.70 in (370 x 370 x 94 mm)				
WEIGHT					
PACKAGED	Model QB-8200-EPA: 15 lbs (6.8 kg) Model QB-8250-EPR: 16.31 lbs (7.4 kg)				
UNPACKAGED	Model QB-8200-EPA: 7.7 lbs (3.5 kg) Model QB-8250-EPR: 9.0 lbs (4.1 kg)				
SAFETY STANDARDS	UL 60950, CAN/CSA-C22.2 No. 60950, IEC 60950, EN 60950				
PACKAGE CONTENTS	<ul style="list-style-type: none"> <li>■ One Tsunami® QB-8200-LNK based on two QB-8200-EPA with three N-type surge protected connectors</li> <li>or One Tsunami® QB-8250-LNK based on two QB-8250-EPR with an integrated 23dBi dual polarized panel antenna</li> <li>■ Two power injector and country specific power cord</li> <li>■ Two Wall / Pole mounting kit</li> <li>■ Two Connector weatherproofing kit (Includes all recommended weatherproofing material)</li> <li>■ Two Serial (RJ-11 to DB9) dongle</li> <li>■ Two Grounding kit</li> <li>■ Two Gigabit PoE Surge Arrestor</li> <li>■ One Quick Installation Guide</li> </ul>				
MTBF & WARRANTY	>250,000 hours & 1-year on parts and labor; ServPak Extended Support available.				

## APPLICATIONS

- **Backhaul to a Central POP**  
Avoid expensive installation and recurring charge of a second wire line backhaul to a remote virtual POP
- **Leased Line Redundancy**  
Eliminate recurring DS-3 leased line charges with one time installation charge of a QuickBridge link
- **Repeater**  
Extend distance or overcome path blockage by adding point-to-point hops
- **High-bandwidth Last Mile Access**  
Use QuickBridge to deliver TLS (Transparent LAN Services) to corporate parks
- **Inter-POP Redundancy**  
Avoid downtimes caused by a wireline backhaul failure by adding a QuickBridge link as an inter-POP redundancy

For detailed technical specifications, please go to <http://proxim.com/products/ptpwireless-backhaul/tsunamir-qb-8200-series>

©2012 Proxim Wireless Corporation. All rights reserved. Proxim is a registered trademark and the Proxim logo and Tsunami® are trademarks of Proxim Wireless Corporation. All other trademarks mentioned herein are property of their respective owners. Specifications are subject to change without notice.

DS\_1112\_QB8200\_A4



Proxim Wireless Corporation  
[www.proxim.com](http://www.proxim.com)